



SAKER TAB-TENSION SERIES

The *Saker Tab-Tension Series* is an electric projection screen draped with our MaxWhite® Fiberglass front projection material that provides excellent color uniformity with a wide viewing angle. It's tab-tension assists in keeping the material from curling on the sides. It includes a pair of wall brackets for a flush wall installation. Also included is a pair of eye-bolt screws that attach to the top of the case for a suspended ceiling installation. Standard features include a wireless 5-12 volt trigger, IR/RF remote control package, and a detachable manual keypad switch.



Screen Material

- MaxWhite® Fiberglass (FG) 1.1 Gain matte white front projection material
- 180° wide viewing angle with diffusion uniformity allows viewers to see a clear picture from any angle
- Not compatible with Ultra/Short-throw Projectors
- Standard black masking borders enhance perceived contrast and absorb projector overshoot
- Black backing eliminates light penetration for superior color reproduction
- Silent operation synchronous motor and low power consumption
- GREENGUARD® and GREENGUARD® Gold Certified | UL 2818
- Available in 100" diagonal size in 4:3 format

Design & Installation

- Flush hidden wall mounts allow screen to slide horizontally for proper centering
- Tab-tension design helps maintain a flat projection surface
- Curved aluminum enamel white case with parallel grooves
- Extra top black masking border for high ceiling installations
- Plug & Play ready, no hardwired installation required
- Mounting hardware kit included for wall or ceiling installation
- Internal Radio Frequency/Infrared receivers with IR, RF remotes
- Includes a detachable 3-way wall switch, Extended IR "eye" sensor, and Wireless 5-12 volt trigger
- 12 volt trigger capable for synchronized screen operation with the projector's power cycle
- 5-year premium manufacturer's warranty