

Outdoor Electric Wireless Pro Series Dimensions Table

Model Number	Diag. Size	Aspect Ratio	Screen Material	Case L (A)	View W (A1)	ceiling bracket hole distance (A2)	Screen W (A3)	L/R black masking (A4)	Weight Bar L (A5)	Distance between end cap to fabric (A6)	Distance between end cap to fabric (A7)	Overall H with ceiling Bracket (B)	View H (B1)	Screen Height (B2)	Top black masking (B3)	Bottom black masking (B4)	End cap W with ceiling bracket (C)	End cap H with ceiling bracket (C1)	Screen Material to Wall Distance (C2)	Weight bar diameter (C3)
Unit: Inch																				
PRO110HT-BAT	110"	16:9	CineWhite®	115.5	95.9	84.0	101.4	1.6	113.3	7.8	6.5	74.2	53.9	69.3	12.0	3.3	4.6	4.9	1.4	0.9
PRO125HT-BAT	125"	16:9	CineWhite®	127.9	109.0	96.4	114.5	1.6	125.7	7.5	6.1	81.6	61.3	76.6	12.0	3.3	4.6	4.9	1.4	0.9
PRO140HT-BAT	140"	16:9	CineWhite®	140.9	122.0	109.4	127.5	1.6	138.7	7.5	6.1	82.9	68.6	78.0	6.0	3.3	4.6	4.9	1.4	0.9
Unit: mm																				
PRO110HT-BAT	110"	16:9	CineWhite®	2933	2435	2133	2575	40	2877	199	164	1885	1370	1760	305	85	118	125	35	23
PRO125HT-BAT	125"	16:9	CineWhite®	3248	2767	2448	2907	40	3192	190	155	2072	1557	1947	305	85	118	125	35	23
PRO140HT-BAT	140"	16:9	CineWhite®	3580	3099	2780	3239	40	3524	190	155	2106	1744	1981	152	85	118	125	35	23

Note: Data Error be ±1"

The listed measurements are for general reference only. Please contact Elite ProAV to verify product design and dimensions before attempting to integrate its products with any structural or furniture modification. Although a manufacturer may offer product advice, it may be taken or disregarded at the integrator's discretion. Elite ProAV will not be held responsible or be otherwise liable for faulty installations. Screen materials may expand and contract slightly over time. Elite ProAV allows a 1.5% tolerance within the viewing surface.

